



FASTER LIFT

FASTER LIFT

- Linear design for easy cleaning
- Lift with single-axis motion and pouch function for dispensing products, also of large dimensions, without tipping over
- Product with drawal door with automatic opening/closing (with anti-crush safety)
- Optimal product withdrawal height: 540 mm
- Patented, energy-saving, slide-in/slide-out refrigeration unit that can be replaced quickly
- Patented lateral refrigeration ventilation for energy savings, condensation and optimal homogenization of temperatures
- 32-bit electronics with USB 2.0 HOST
- Power Led illumination with Energy Saving
- Programming, cloning, and Audit functions using a standard USB pen drive
- Graphic colour display 480x272 pixel with the possibility of a personalised slide shows and/or visualization of supplementary information (ex: product ingredients and nutritional value)
- Ready for easy installation of optional Drawer Display Kit and Push Drawer
- Rieda RS1 Lock
- Easy Click System: for configuring the machine quickly and easily without any need for technical instruments
- Illuminated keyboard
- Standard anti-vandal coin return



Description		Faster LIFT 1050
Dimensions mm (H x L x P)	mm	1830 x 1060 x 790
Size with door open	mm	1810
Standard number of drawers /max	n°	6/7
Min internal temperature		+3°C with fridge safety on the 3 lower drawers
Power supply	V/Hz	230/50
Rated fridge power	W	450
Consumption Eva-Emp 3.0a idle mode	Wh/h	228
Weight	Kg	345
Refrigeration system	Compact (compression type, class N) - Ventilated evaporator - Cyclical defrosting	
Display	pixel	480 x 272
Protocols		MDB/ Executive
Colour		Black RAL 9005 and aluminium

Fas International Spa
Via Lago di Vico, 60
36015 Schio · Vicenza · Italy
T +39 0445 502011

F +39 0445 502.010
info@fas.it
www.fas.it

